

3M™ Skull Screws™ Earplugs

Technical Data Sheet

Description

3M™ Skull Screws™ push-to fit uncorded foam earplugs sport the tough look of threaded metal, but feel of soft foam, while offering push-to-fit convenience and noise attenuation with attitude. Effective hearing protection and compliance with a clean, easy twist.

Key Features

- Tough look of threaded metal, but feel of soft foam
- Push-to-fit style means no earplug roll down required
- Foam tips stay clean, even when your hands are dirty
- SLC₈₀ 26dB

Applications

The 3M™ Skull Screws™ earplugs are ideal for high noise exposure levels, and are ideally suited to provide protection against all noise frequencies in a wide range of industrial workplace and leisure environment. Examples of typical applications include:

- Automotive
- Chemical & pharmaceutical manufacture
- Construction
- Heavy engineering
- Metal processing
- Textile manufacture
- Woodworking

Standards

These hearing protectors have been produced to comply with the requirements of the Australian /New Zealand Standard AS/NZS 1270:2002.



Materials

The following materials are used in the manufacture of this product.

Component	Material
Earplugs	Polyurethane
Cord	PVC

Storage

Store in an area free of contamination.

Do not leave your hearing protection device in areas or locations where it can be exposed to damage or contamination.

Sunlight is particularly damaging as UV light can have a detrimental effect on the materials the product is made from.

Chemical contamination can also have a serious effect on product integrity and decontamination after use is recommended.

Use a suitable storage container especially if left in a vehicle. This will protect the hearing protection device from damage and extend its working life.



Attenuation Data

Class 5	SLC ₈₀ Value is 26.0						
Frequency (HZ)	125	250	500	1000	2000	4000	8000
Mean Attenuation	26.7	26.6	28.5	32.5	37.3	40.5	43.4
Standard Deviation	8.9	8.8	9.2	7.8	4.6	5.4	8.1

Hearing protector class 5 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to 105dB(A) assuming an 85dB(A) criterion.

A lower criterion may require a higher protector class.

Mean = Mean attenuation value derived from testing in accordance with AS/NZS 1270:2002 SD = Standard Deviation derived from testing in accordance with AS/NZS 1270:2002 Mean - SD = Mean attenuation value minus Standard Deviation SLC(80) = Single number rating commonly used in Australia and New Zealand to compare acoustic performance of hearing protectors. The subscript '80' indicates that in well managed hearing protector programs, the protection provided is expected to equal or exceed the SLC(80) in 80% of protector-wearer noise spectrum combinations. Class = A simplified process for selecting hearing protectors based on the wearers 8-hour equivalent continuous A-weighted sound pressure level.

Ordering Information

3M Code	Model #	Description
70071515640	P1300	3M Skull Screws Uncorded
70071515632	P1301	3M Skull Screws Corded

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Australia Pty Ltd
Personal Safety Division
Bldg A, 1 Rivett Road
North Ryde NSW 2113
TechAssist Helpline: 1800 024 464
Customer Service: 1300 363 565
Email: techassist@mmm.com
Web: www.3M.com/au/ppesafety

3M New Zealand Ltd
Personal Safety Division
94 Apollo Drive, Rosedale
Auckland 0632
TechAssist Helpline: 0800 364 357
Customer Service: 0800 252 627
Email: techassist@mmm.com
Web: www.3M.com/nz/ppesafety

3M is a trademark of 3M Company.
Please recycle. Printed in Australia.
© 3M 2019. All rights reserved.
AV011485370