uvex

uvex Hand Protection System

uvex u-chem 3100

- · Supported nitrile chemical glove
- Cotton liner
- Sand grip palm
- · Outstanding grip characteristics
- · Excellent dexterity
- Excellent anatomical hand form for excellent comfort
- EN ISO 374-1:2016 (AJKLMO)
- EN 388:2016 (4121X)



EN ISO 374-1:2016/Type A





uvex Point of Difference	Benefits
Sand Grip Palm	Provides outstanding grip for wet and oily environments, along with a high level of abrasion resistance for long product service life.
Supported cotton liner	The cotton liner provides a higher level of wearer comfort than would a synthetic material of flock lining.

Permeation resistance of type A: at least 30 minutes each with at least 6 test chemicals.

- A = Methanol level 2 > 30 minutes
- J = n-heptane level 5 > 240 minutes
- K = Sodium hydroxide 40% level 6 > 480 minutes
- L = Sulphuric acid 96% level 2 > 30 minutes
- M Nitric acid 65% level 3 > 60 minutes
- O Ammonium hydroxide 25% level 2 > 30 minutes

Target Applications (but not limited to):

- Water treatment (city and shire councils, water authorities)
- · Janitorial/Cleaning
 - Cleaning bathroom/restrooms
 - Dish rinsing and washing
- · Engineering maintenance
 - Parts washes
 - Vehicle wash down
 - Handling POL products (petroleum, oils and lubricants)
- · Refining (i.e. alumina, petrochemical etc.)
 - Excellent protection against sodium hydroxide (caustic acid)
 - Process sampling
 - Decanting chemicals (degreasers, process additives etc.)
- Construction/Trades
 - Form work / Concreting / Plumbing / Rendering

Part Numbers:

- size 8 60968F1
- size 9 60968F2
- size 10 60968F3

Packaging:

- · 10 pairs per bundle
- · 100 pairs per carton

Barcodes:

- · size 8 60968F1 4048612051122
- size 9 60968F2 4048612051139
- · size 10 60968F3 4048612051146